

ICNIRP Measurement Report

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)¹, with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 420 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor² of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

Date of Survey:	19/04/23	Time Survey completed:	13:13
Survey address:	Coventry CV6		

Measurement equipment		Serial number	Calibration Date
Meter	Keysight Fieldfox N9915A Spectrum Analyser	MY56072612	14/09/2022
Probe	Agos Aria-6000 Antenna	60001117	28/11/2022
Cabling	1.7m Cable	1319	28/11/2022

¹ <https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf>

² The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.

Mobile bands covered by this report

Frequency Band	Frequency	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

Notes

* This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations.

** All other frequencies between 420 MHz and 6 GHz.

Survey locations

The survey was conducted within the area shown in the map below. Measurements were taken at six locations and are presented in the following pages of this report.



Map data: © Google

Location 1

Measurement time:	11:50
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.0010
800 MHz	0.0006
900 MHz	0.0009
1400 MHz	0.0004
1800 MHz	0.0005
1900 MHz	0.0002
2100 MHz	0.0005
2300 MHz	0.0004
2600 MHz TDD	0.0003
2600 MHz FDD	0.0002
3.4 GHz	0.0019
3.8 GHz	0.0043
Others	0.0676
Total	0.0787

Location 2

Measurement time:	12:01
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.0011
800 MHz	0.0559
900 MHz	0.1033
1400 MHz	0.0004
1800 MHz	0.0020
1900 MHz	0.0002
2100 MHz	0.0078
2300 MHz	0.0008
2600 MHz TDD	0.0003
2600 MHz FDD	0.0002
3.4 GHz	0.0022
3.8 GHz	0.0045
Others	0.0734
Total	0.2520

Location 3

Measurement time:	12:13
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.0011
800 MHz	0.0060
900 MHz	0.0036
1400 MHz	0.0004
1800 MHz	0.0010
1900 MHz	0.0002
2100 MHz	0.0019
2300 MHz	0.0036
2600 MHz TDD	0.0003
2600 MHz FDD	0.0002
3.4 GHz	0.0026
3.8 GHz	0.0046
Others	0.0722
Total	0.0977

Location 4

Measurement time:	12:22
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.0011
800 MHz	0.0461
900 MHz	0.0407
1400 MHz	0.0004
1800 MHz	0.0014
1900 MHz	0.0002
2100 MHz	0.0046
2300 MHz	0.0081
2600 MHz TDD	0.0003
2600 MHz FDD	0.0002
3.4 GHz	0.0033
3.8 GHz	0.0048
Others	0.0752
Total	0.1862

Location 5

Measurement time:	12:49
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.0011
800 MHz	0.0492
900 MHz	0.0169
1400 MHz	0.0004
1800 MHz	0.0011
1900 MHz	0.0002
2100 MHz	0.0016
2300 MHz	0.0019
2600 MHz TDD	0.0003
2600 MHz FDD	0.0002
3.4 GHz	0.0022
3.8 GHz	0.0045
Others	0.0701
Total	0.1495

Location 6

Measurement time:	13:07
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.0011
800 MHz	0.0219
900 MHz	0.0194
1400 MHz	0.0004
1800 MHz	0.0008
1900 MHz	0.0002
2100 MHz	0.0043
2300 MHz	0.0038
2600 MHz TDD	0.0003
2600 MHz FDD	0.0002
3.4 GHz	0.0021
3.8 GHz	0.0046
Others	0.0714
Total	0.1305

Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.