

# ICNIRP Measurement Report

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)<sup>1</sup>, with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 420 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor<sup>2</sup> of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

<b>Date of Survey:</b>	18/03/2024	<b>Time Survey completed:</b>	14:22
<b>Survey address:</b>	York YO31		

Measurement equipment		Serial number	Calibration Date
<b>Meter</b>	Keysight Fieldfox N9915A Spectrum Analyser	MY50672594	02/11/2023
<b>Probe</b>	Agos Aria-6000 Antenna	60001024	30/03/2021
<b>Cabling</b>	1.7m Cable	1383	12/11/2023

---

<sup>1</sup> <https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf>

<sup>2</sup> The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.

## Mobile bands covered by this report

Frequency Band	Frequency Range	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

\* This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations. \*\* All other frequencies between 420 MHz and 6 GHz.

## Survey locations

The survey was conducted within the area shown in the map below. Measurements were taken at six locations and are presented in the following pages of this report.



**Location 1**

<b>Measurement time:</b>	<b>13:28</b>
<b>Frequency band</b>	<b>Percentage of the ICNIRP reference levels for general public exposure</b>
700 MHz	0.00154
800 MHz	0.04621
900 MHz	0.03235
1400 MHz	0.00035
1800 MHz	0.01381
1900 MHz	0.00016
2100 MHz	0.01971
2300 MHz	0.00349
2600 MHz TDD	0.00031
2600 MHz FDD	0.00017
3.4 GHz	0.00194
3.8 GHz	0.00403
Others	0.14539
<b>Total</b>	<b>0.26946</b>

**Location 2**

<b>Measurement time:</b>	<b>13:46</b>
<b>Frequency band</b>	<b>Percentage of the ICNIRP reference levels for general public exposure</b>
700 MHz	0.00121
800 MHz	0.00650
900 MHz	0.02201
1400 MHz	0.00040
1800 MHz	0.00640
1900 MHz	0.00018
2100 MHz	0.00532
2300 MHz	0.00156
2600 MHz TDD	0.00036
2600 MHz FDD	0.00019
3.4 GHz	0.00244
3.8 GHz	0.00466
Others	0.16427
<b>Total</b>	<b>0.21550</b>

**Location 3**

<b>Measurement time:</b>	<b>13:53</b>
<b>Frequency band</b>	<b>Percentage of the ICNIRP reference levels for general public exposure</b>
700 MHz	0.00171
800 MHz	0.02915
900 MHz	0.03766
1400 MHz	0.00042
1800 MHz	0.00165
1900 MHz	0.00019
2100 MHz	0.00160
2300 MHz	0.00134
2600 MHz TDD	0.00038
2600 MHz FDD	0.00021
3.4 GHz	0.00239
3.8 GHz	0.00490
Others	0.17094
<b>Total</b>	<b>0.25254</b>

**Location 4**

<b>Measurement time:</b>	<b>14:01</b>
<b>Frequency band</b>	<b>Percentage of the ICNIRP reference levels for general public exposure</b>
700 MHz	0.00168
800 MHz	0.01763
900 MHz	0.00996
1400 MHz	0.00042
1800 MHz	0.00320
1900 MHz	0.00019
2100 MHz	0.00135
2300 MHz	0.00091
2600 MHz TDD	0.00039
2600 MHz FDD	0.00021
3.4 GHz	0.00226
3.8 GHz	0.00504
Others	0.17435
<b>Total</b>	<b>0.21759</b>

**Location 5**

<b>Measurement time:</b>	<b>14:08</b>
<b>Frequency band</b>	<b>Percentage of the ICNIRP reference levels for general public exposure</b>
700 MHz	0.00189
800 MHz	0.03349
900 MHz	0.02674
1400 MHz	0.00043
1800 MHz	0.00326
1900 MHz	0.00020
2100 MHz	0.00431
2300 MHz	0.00144
2600 MHz TDD	0.00039
2600 MHz FDD	0.00023
3.4 GHz	0.00233
3.8 GHz	0.00513
Others	0.17807
<b>Total</b>	<b>0.25791</b>

**Location 6**

<b>Measurement time:</b>	<b>14:16</b>
<b>Frequency band</b>	<b>Percentage of the ICNIRP reference levels for general public exposure</b>
700 MHz	0.00197
800 MHz	0.05027
900 MHz	0.10492
1400 MHz	0.00043
1800 MHz	0.00300
1900 MHz	0.00020
2100 MHz	0.00280
2300 MHz	0.00106
2600 MHz TDD	0.00040
2600 MHz FDD	0.00026
3.4 GHz	0.00232
3.8 GHz	0.00520
Others	0.18329
<b>Total</b>	<b>0.35612</b>

*Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.*