

ICNIRP Measurement Report

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)¹, with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 420 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor² of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

Date of Survey:	12/12/2024	Time Survey completed:	11:11
Survey address:	Bellshill ML4		

Measurement equipment		Serial number	Calibration Date
Meter	Keysight Fieldfox N9915A Spectrum Analyser	MY57271744	31/12/2023
Probe	Agos Aria-6000 Antenna	ARIA-6000-1089	31/12/2023
Cabling	1.7m cable	1240	31/12/2023

¹ <https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf>

² The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.

Mobile bands covered by this report

Frequency Band	Frequency Range	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

** This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations. ** All other frequencies between 420 MHz and 6 GHz.*

Survey locations

The survey was conducted within the area shown in the map below. Measurements were taken at six locations and are presented in the following pages of this report.



Location 1

Measurement time:	10:15
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.00364
800 MHz	0.01940
900 MHz	0.00080
1400 MHz	0.01801
1800 MHz	0.03494
1900 MHz	0.00019
2100 MHz	0.02131
2300 MHz	0.00041
2600 MHz TDD	0.00031
2600 MHz FDD	0.00240
3.4 GHz	0.00230
3.8 GHz	0.00270
Others	0.32818
Total	0.43459

Location 2

Measurement time:	10:24
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.00271
800 MHz	0.02571
900 MHz	0.00069
1400 MHz	0.00752
1800 MHz	0.01727
1900 MHz	0.00019
2100 MHz	0.01012
2300 MHz	0.00042
2600 MHz TDD	0.00032
2600 MHz FDD	0.00078
3.4 GHz	0.00157
3.8 GHz	0.00269
Others	0.17659
Total	0.24658

Location 3

Measurement time:	10:33
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.00632
800 MHz	0.02234
900 MHz	0.00067
1400 MHz	0.01634
1800 MHz	0.00595
1900 MHz	0.00020
2100 MHz	0.00441
2300 MHz	0.00042
2600 MHz TDD	0.00032
2600 MHz FDD	0.00058
3.4 GHz	0.00197
3.8 GHz	0.00288
Others	0.15492
Total	0.21731

Location 4

Measurement time:	10:42
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.00410
800 MHz	0.02429
900 MHz	0.00068
1400 MHz	0.01111
1800 MHz	0.01061
1900 MHz	0.00019
2100 MHz	0.00327
2300 MHz	0.00042
2600 MHz TDD	0.00031
2600 MHz FDD	0.00079
3.4 GHz	0.00137
3.8 GHz	0.00271
Others	0.14973
Total	0.20958

Location 5

Measurement time:	10:53
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.00340
800 MHz	0.01424
900 MHz	0.00065
1400 MHz	0.00603
1800 MHz	0.00298
1900 MHz	0.00020
2100 MHz	0.00513
2300 MHz	0.00041
2600 MHz TDD	0.00032
2600 MHz FDD	0.00114
3.4 GHz	0.00164
3.8 GHz	0.00281
Others	0.17024
Total	0.20920

Location 6

Measurement time:	11:05
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.00751
800 MHz	0.03405
900 MHz	0.00084
1400 MHz	0.02830
1800 MHz	0.03262
1900 MHz	0.00019
2100 MHz	0.03086
2300 MHz	0.00042
2600 MHz TDD	0.00032
2600 MHz FDD	0.00400
3.4 GHz	0.00339
3.8 GHz	0.00285
Others	0.35506
Total	0.50039

Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.