

ICNIRP Measurement Report

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)¹, with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 420 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor² of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

Date of Survey:	26/11/2024	Time Survey completed:	16:22
Survey address:	Sutton Coldfield B72		

Measurement equipment		Serial number	Calibration Date
Meter	Keysight Fieldfox N9915A Spectrum Analyser	MY59221930	11/04/2024
Probe	Agos Aria-6000 Antenna	ARIA6000-1158	16/04/2024
Cabling	1.7m cable	1458	16/04/2024

¹ <https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf>

² The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.

Mobile bands covered by this report

Frequency Band	Frequency Range	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

* This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations. ** All other frequencies between 420 MHz and 6 GHz.

Survey locations

The survey was conducted within the area shown in the map below. Measurements were taken at six locations and are presented in the following pages of this report.



Location 1

Measurement time:	15:09
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.00048
800 MHz	0.04421
900 MHz	0.00034
1400 MHz	0.00013
1800 MHz	0.01542
1900 MHz	0.00006
2100 MHz	0.00099
2300 MHz	0.00013
2600 MHz TDD	0.00012
2600 MHz FDD	0.00026
3.4 GHz	0.00072
3.8 GHz	0.00129
Others	0.01810
Total	0.08224

Location 2

Measurement time:	15:21
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.00043
800 MHz	0.00139
900 MHz	0.00017
1400 MHz	0.00012
1800 MHz	0.00248
1900 MHz	0.00006
2100 MHz	0.00085
2300 MHz	0.00011
2600 MHz TDD	0.00011
2600 MHz FDD	0.00020
3.4 GHz	0.00064
3.8 GHz	0.00106
Others	0.01160
Total	0.01923

Location 3

Measurement time:	15:38
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.00035
800 MHz	0.00514
900 MHz	0.00124
1400 MHz	0.00011
1800 MHz	0.00050
1900 MHz	0.00006
2100 MHz	0.00042
2300 MHz	0.00011
2600 MHz TDD	0.00010
2600 MHz FDD	0.00009
3.4 GHz	0.00060
3.8 GHz	0.00084
Others	0.00928
Total	0.01884

Location 4

Measurement time:	15:52
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.00046
800 MHz	0.00699
900 MHz	0.00132
1400 MHz	0.00015
1800 MHz	0.01413
1900 MHz	0.00005
2100 MHz	0.00158
2300 MHz	0.00014
2600 MHz TDD	0.00010
2600 MHz FDD	0.00012
3.4 GHz	0.00065
3.8 GHz	0.00086
Others	0.00661
Total	0.03316

Location 5

Measurement time:	16:02
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.00124
800 MHz	0.00522
900 MHz	0.00055
1400 MHz	0.00043
1800 MHz	0.02175
1900 MHz	0.00005
2100 MHz	0.00237
2300 MHz	0.00011
2600 MHz TDD	0.00009
2600 MHz FDD	0.00074
3.4 GHz	0.00080
3.8 GHz	0.00092
Others	0.00578
Total	0.04008

Location 6

Measurement time:	16:16
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.00016
800 MHz	0.00950
900 MHz	0.00026
1400 MHz	0.00010
1800 MHz	0.00756
1900 MHz	0.00005
2100 MHz	0.00066
2300 MHz	0.00010
2600 MHz TDD	0.00009
2600 MHz FDD	0.00019
3.4 GHz	0.00053
3.8 GHz	0.00053
Others	0.00496
Total	0.02469

Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.